

SPARTAN FELT CO., INC.

AMS PAD

DESCRIPTION:	White fiber based resin treated polyurethane pad for diverse polishing applications and surfaces. The fiber material makes excellent interconnecting cellular structures, which make the pad highly durable and dimensionally stable. This material is designed for rapid stock removal and superb surface finishes.
FOR USE ON:	Silicon Wafers, Cadmium Telluride, Gallium Arsenide, Stainless Steel
DUROMETER:	Shore C Scale 60
COMPRESSION %:	4-6% (1/2 pound force displacement)
DENSITY:	.42 g/cm ³
THICKNESS:	.050", .090" and .125"
DIAMETER:	Up to 53" in Sheets or Pads
SURFACE PREPARATION:	Plain, Perforated or Embossed.
BACKINGS:	Easy Apply/Remove PSA Is Standard. High Temperature PSA Magnetic Backing are Available Upon Request
IMPREGNATIONS:	Abrasive Impregnates in limited styles.
CAN REPLACE:	SUBA X and SUBA 500
PERFORMANCE:	AMS PAD is our most popular hard class pad. It is a superbly durable synthetic fiber pad, effective under light pressure. Capillary action fiber structure. Open pore structure, reduced compressibility.



Spartan felt company, inc.

DRAWER 1932

SPARTANBURG, SOUTH CAROLINA 29304

(864) 576-7919

FAX (864) 574-1507