

HPC-4560 POLISHING MATERIAL



Surface Preparation Division

DESCRIPTION:	White or color fiber based resin treated polyurethane pad for diverse polishing applications and surfaces. The fiber material makes excellent interconnecting cellular structures, which make the pad highly durable and dimensionally stable. This material is designed for rapid stock removal and superb surface finishes. HPC-4560 is less absorbent than HPC4545.
FOR USE ON:	Glass, Ceramic, Fused Silica, and Sapphire
DUROMETER:	Shore C Scale 60
COMPRESSION %:	3-5% (1/2 pound force displacement)
DENSITY:	.46 g/cm ³
THICKNESS:	.050" and .150"
DIAMETER:	Up to 53" in Sheets or Pads
SURFACE PREPARATION:	Plain, Perforated or Embossed.
BACKINGS:	Easy Apply/Remove PSA Is Standard. High Temperature PSA Magnetic Backing are Available.
IMPREGNATIONS:	Abrasive Impregnates in limited styles.
CAN REPLACE:	SUBA X and SUBA 500
PERFORMANCE:	HPC-4560 is an enhanced version of our most popular hard class pad HPC4545. It is a superbly durable synthetic fiber pad, effective under light pressure. Capillary action fiber structure. Open pore structure, reduced compressibility.

SPARTAN FELT CO. – POLISHING PAD GROUP

151 Felt Drive, Roebuck, SC 29376

TEL: 864-576-7919

www.spartanfelt.com/polishingpads

e-mail: jwelry@spartanfelt.com

