



## Spartan Spar-Lon-Red Pads

DESCRIPTION:	Spartan Spar-Lon-Red Polishing Pads
FOR USE ON:	This final polishing pad can be used on sapphire, glass, plastics, ceramics, and metals with a variety of abrasive slurries.
DUROMETER:	80° Shore A
COMPRESSION:	4% (2 pound Displacement)
DENSITY:	0.40 g/cm <sup>3</sup>
THICKNESS:	.050" +/- .001"
DIAMETER:	Up to 48" Pads
SURFACE PREPARATION:	Plain Pads (no perforations or embossing possible)
BACKINGS:	PSA or magnetic backings
IMPREGNATIONS:	No impregnations; this is a final polish pad.
CAN REPLACE:	Eminess Politex products but it is a flocked pad and not poromeric.
PERFORMANCE:	This is a soft polishing pad (red, flocked) on a cotton substrate (woven) plus PSA (standard or hydrocarbon resistant). Excellent "super-polished" surfaces can be achieved with the correct alumina, diamond or cerium slurries.

### SPARTAN FELT CO. – POLISHING PAD GROUP

151 Felt Drive, Roebuck, SC 29376

TEL: 864-576-7919

[www.spartanfelt.com/polishingpads](http://www.spartanfelt.com/polishingpads)

e-mail: [jwerty@spartanfelt.com](mailto:jwerty@spartanfelt.com)

